

Retaining magnets

disc-shaped, with female thread, with rubber jacket

SPECIFICATION

Steel part
zinc plated
Material of the magnet
NdFeB **ND**
Neodymium, iron, boron
temperature resistant up to 80 °C
Rubber jacket
Elastomer (TPE)
80 shore A ≈
black **SW**
white **WS**

INFORMATION

The retaining magnets with rubber jacket GN 51.2 form a system together with the steel part that shields and strengthens the magnet, optimally concentrating the magnetic flux on the rubberized magnetic surface.

The rubber protects sensitive surfaces from being damaged by the magnet and also delivers a high friction coefficient, resulting in high lateral displacement forces.

- More information to retaining magnets (see page 2022)

TECHNICAL INFORMATION

- Elastomer characteristics (see page A32)




ACCESSORY


- Holding discs GN 70 (see page 2051)
- Adhesive discs GN 70.1 (see page 2051)

ON REQUEST

- other colors
- other Shore hardnesses



View of magnetic surface



GN 51.2

Description	d1	d2	d3	h	l	t min.	Nominal magnetic forces in N	⚖
GN 51.2-ND-12-M4-SW	12	M 4	8	7	7.5	6	13	6
GN 51.2-ND-12-M4-WS	12	M 4	8	7	7.5	6	13	6
GN 51.2-ND-18-M4-SW	18	M 4	8	6	5.5	5	37	9
GN 51.2-ND-18-M4-WS	18	M 4	8	6	5.5	5	37	9
GN 51.2-ND-22-M4-SW	22	M 4	8	6	5.5	5	58	13
GN 51.2-ND-22-M4-WS	22	M 4	8	6	5.5	5	58	13
GN 51.2-ND-31-M4-SW	31	M 4	8	6	5.5	5	89	22
GN 51.2-ND-31-M4-WS	31	M 4	8	6	5.5	5	89	22
GN 51.2-ND-43-M4-SW	43	M 4	8	6	4.5	5	100	33
GN 51.2-ND-43-M4-WS	43	M 4	8	6	4.5	5	100	33
GN 51.2-ND-43-M5-SW	43	M 5	8	6	4.5	7	100	37
GN 51.2-ND-43-M5-WS	43	M 5	8	6	4.5	7	100	37
GN 51.2-ND-57-M5-SW	57	M 5	10	7.5	7	8	200	83
GN 51.2-ND-57-M5-WS	57	M 5	10	7.5	7	8	200	83
GN 51.2-ND-66-M5-SW	66	M 5	10	8.5	6.5	8	250	105
GN 51.2-ND-66-M5-WS	66	M 5	10	8.5	6.5	8	250	105
GN 51.2-ND-88-M8-SW	88	M 8	12	8.5	8.5	11	550	192
GN 51.2-ND-88-M8-WS	88	M 8	12	8.5	8.5	11	550	192